

**C4** 55 L - 1.9 cubic feet

C41 White Frame Clear Glass Door



C41 Top Dry Section



C41 Opaque White Glass Door



Available as Automatic, Semi-Automatic and Upgradeable

**Product** 

41 Sensors, 31 Product Types Also Available with Big Bottle Balcony

**Door Type** 

Foam-Core Door Panel **Wood Door** Glass Door: Clear, Opaque, or with your Logo

**Dimensions** 

W: 17.72 in - 450 mm H: 22.44 in - 570 mm

D: 20.08 in - 510 mm with compressor

**Optional** 

**Integrated Dry Sections External Sections for Dry Products** 



C41 Opaque Black Glass Door



# minibarsolution

# barted

# **Technical**

# **Specifications**

## Standard C41

Shelves with Sensors

10 bottles 10 cans

5 bottles (laid down) Adjustable shelves (No tools needed)

**Door Balconies** with Sensors

2 x 8 miniatures/

snacks

big bottle available

Server OS

2012 R2 and Up

Software

Web-based

**Interface Types** 

TCP IP/RS 232

Available for all PMS

Data

Communication

Ethernet

ZigBee (wireless) Wi-Fi (wireless)

Database **Engine** 

Microsoft SQL Server 2012 and

Up

**Cooling Unit** 

Compressor

**Absorption** 

Sensors

Infrared

Microswitches

Magnetic

Voltage

110-240 VAC /

50-60 HZ



### Integrated dry sections available

### 38 inch<sup>2</sup> / 240 cm<sup>2</sup> clear area for airflow

The minibar must be properly ventilated. A channel for air circulation under the minibar, passing up and over the cooling unit and exhausting out from the minibar is mandatory. A 50 mm free space is recommended between the wall or cabinet back and cooling unit.















Sartech copyright 06/2019