

solution

 \bigcirc

eDrawer

45 L - 1.8 cubic feet

Features

- Stocking capacity of up to 23 product types, 23 sensors
- Compressor cooling unit
- Web/Windows-based software
- CESS (computerized energy) saving system) automatically controls temperature
- Automatic posting of guest charges to PMS
- Remote in-room controls
- Automatic expiration date management
- Remote locking door (can be deactivated)

Door Options

- Use your own millwork manufacturer door or one of Bartech's
- Non-Bartech millwork door's max. weight cannot exceed 4kg/8 lbs

Optional Features

 External sections for dry products



eDrawer

Available as Automatic, Semi-Automatic and Manual

Dimensions

W: 21.70 in - 550 mm H: 16.70 in - 423 mm D: 18.90 in - 480 mm (Dimensions without door panel and handle)

Door Type

Wood Door Glass Door: Clear, Opaque, or with your Logo

Voltage

110 - 240 VAC / 50-60 HZ

Options

External sections for dry products

solution minibar

Technical

Specifications

Standard eDrawer

Shelves with Sensors

Up to 15 bottles Adjustable dividers (No tools needed)

Dry Product Storage

12 miniatures/

snacks

Server OS

2012 R2 and Up

Software

Web-based

Windows

Interface Types

TCP IP/RS 232

Available for all PMS

Data

Communication

Ethernet Twisted Pair ZigBee (wireless) Wi-Fi (wireless)

Database

Engine

Microsoft SQL Server 2012 and


Up


Sensors Infrared

Voltage 110-240 VAC /

50-60 HZ

Width: 21.70 in - 550 mm Height: 16.70 in 423 mm





External dry sections available

38 inch² / 240 cm² clear area for airflow

The minibar must be properly ventilated. A channel for air circulation under the minibar, passing up and over the cooling unit and exhausting out from the minibar is mandatory. A 50 mm free space is recommended between the wall or cabinet back and cooling unit.

